

ULTRAMAT 23 Gas Analyzer – Unique solution for Biogas applications

Continuous measurements for better process control



The well-proven ULTRAMAT 23 gas analyzer extended with an hydrogen sulfide (H_2S) sensor provides the perfect, simple and complete solution for analysis in biogas plants.

It is a unique solution that combines the measurement of infrared active gases with oxygen and H_2S sensors in a single unit to determine process states in the plant by continuous analysis of the gas composition.

ULTRAMAT 23

www.usa.siemens.com/processanalytics

SIEMENS

The ULTRAMAT 23 for biogas applications simultaneously measures 4 gas components: 2 infrared active gases, methane (CH₄) and carbon dioxide (CO₂), and oxygen (O₂) and hydrogen sulfide (H₂S) using electrochemical cells. The measurements of all components are made continuously allowing better process control which results not only in an economically optimized process but also in a better product quality.

The H₂S sensor is integrated in the 19" rack ULTRAMAT 23 analyzer, which can also be mounted in a compact enclosure including a sample conditioning system (IP54).

The autocalibration feature of the ULTRAMAT 23 and the low drift of the H₂S sensor enable maximum ease of use and minimum maintenance attention for effective, economic and reliable plant operation.

Applications

- Process control of the fermenter for biogas generation (crude side and clean side)
- Gas engine monitoring (electrical and thermal energy generation) for motor protection
- Optimization of methane yield and feed (biogas power generation)
- Quality control of biogas fed into commercial gas distribution network

Technical specifications, H ₂ S channel	
Smallest measuring range	0...500 vpm
Largest measuring range	0...5000 vpm
Drift	< 1 % per month
Repeatability	< 4 % of full scale
Resolution	0.2% of full scale
Delayed display (t90-time)	< 80 s at approximately 1 ... 1.2 l/min sample gas flow
Permissible pressure fluctuations	750...1200 hPa
Permissible ambient temperature	5 ...40° C
Sensor life cycle	ca. 12 months

Benefits

- Better process control – continuous measurements of all four gas components including CH₄ and H₂S in one compact analyzer
- Improved durability and process control even under extreme conditions – long operating life of the H₂S sensor even at high concentrations
- Low maintenance and improved safety – no dilution of the measured gas, no purging of the H₂S sensor
- Improved safety – measurement of flammable gases, as found in biogas plants (e.g. 70 % CH₄) is allowed (TÜV certificate)
- Reduced calibration effort and costs – minimal drift of the H₂S at the endpoint (< 1 % per month), autocalibration with ambient air
- Simplified process integration, remote operation and control – open interface architecture (RS485, RS 232; PROFIBUS PA/DP, SIPROM GA)
- Service information and logbook – preventive maintenance; help for service and maintenance personnel, cost savings

For more information, please contact:

Siemens Industry, Inc.
7101 Hollister Road
Houston, TX 77040
Phone: 713-939-3755
Email: cgainquiry.industry@siemens.com

Siemens Industry, Inc.
Industry Automation Division
3333 Old Milton Parkway
Alpharetta, GA 30005

1-800-241-4453
info.us@siemens.com

www.usa.siemens.com/processanalytics

Subject to change without prior notice
Order No.: PIAFL-00039-0211
Printed in USA
© 2011 Siemens Industry, Inc.

The information provided in this flyer contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.