

## Compact UV -Tekniset tiedot

### Floodlight

Distribution angle (beam) approx. 45°  
Irradiance  $\approx 3\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Midlight

Distribution angle (beam) approx. 20°  
Irradiance  $\approx 8\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Spotlight

Distribution angle (beam) approx. 3.5°  
Irradiance  $\approx 45\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Handles

- Mounting Brackets
- Top Handle
- Pistol Handle

### Voltage

- 100 VAC, 115 VAC, 230 VAC
- 12/24 VDC, operated from external 12/24 via included cigarette cable or from mains via PSU (PSU not included)
- Input Power: 43 W
- Output Power: 35 W

### Weight & Cables

- Weight: 2.25 kilos (5 lbs)
- Cable length: 2 meters (2.2 yd)

### Additional Information

- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 2 000 hrs
- Wavelength: UV-A, peak at 365nm
- Start-up time: full power after 5-15 sec
- Material in housing: anodized aluminum, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL/cETL approved
- IP65 classified, dust and temporary water jetting proof