

Product Overview

Gas Fired Igniters

Pilot Burners

Ignition Lances for Flares, Furnaces and Boilers





Introduction

For more than 65 years Smitsvonk has been making low-tension high-energy ignition and control systems for industrial combustion processes. These electrical and electronic ignition systems are applied world-wide. They are characterized by a high degree of reliability under demanding conditions. Ignition is not effected by dirt, humidity, extreme temperatures or aggressive gases.

History



The company was founded in 1947 by Mr. Wietze Beye Smits. He was the inventor of the High-Energy (Low-Tension) Ignition System.

Before the production of industrial ignition systems started in 1960 Smitsvonk was a laboratory for ignition systems for the automobile industry. Smitsvonk became a member of DURAG GROUP in 2006.











The Smitsvonk Ignition Principle

Smitsvonk's low tension high energy ignition system is designed to meet the requirements of reliable ignition for many industrial applications. The system is based upon the principle of a capacitor discharge over a special discharge surface. This surface consists of an isolator with semiconductor properties. The isolator and positive and negative electrodes are integrated into a high temperature resistant spark plug. When a charged capacitor is connected, it will be dis-

charged via the spark plug producing sparks, even under wet or soiled conditions.

Process step by step

- 1. Charge capacitor
- 2. Capacitor connected to spark plug through high voltage thyristor
- 3. As capacitor discharges a current forms across the semi conductor surface of the spark plug
- 4. The area above the insulator becomes ionised
- 5. Resulting flame shaped spark forms a plasma. Current from 300–1000 A in 5 to 15 μs

Applications

- Ground and elevated flares
- Industrial furnaces and boilers
- Pulverized coal fired power plants
- Portable igniters
- Waste incinerators
- Gas engines/turbines



This system has the following advantages

- Moisture, dirt, oil and grease will not effect the ignition
- Not limitation for cable length
- Low power consumption
- Insensitive to process pressure
- Self cleaning spark plug surface, due to flame shaped spark
- Tension is low in comparison to traditional ignition sources
- Easy construction for explosion proof execution.

The system comprises:

- A power supply with varying capacities
- Control electronics with variable pulse frequencies
- A thyristor
- A connection cable
- Smitsvonk low tension spark tip.







Flare Ignition Systems

Flaring systems in a refinery, petrochemical plant or steel plant ensure the safe and efficient disposal of relieved gases. A flare is expected to operate twenty-four hours a day. The flare system must be in service for several years without a need for maintenance. Therefore proper design and operation are extremely important.

Ignition of the waste gases can be done by pilot burners (flame) or for some applications by ignition lances (spark).

The ignition system must reliably ignite the waste gas of the flare. If the ignition system fails, unburned hydrocarbons and/or toxic gases could be released into the atmosphere.



SMITSVONK Flame Front Generator Panel with Extra High Energy Ignition



DURAG smart solutions for GROUP combustion and environment



Smitsvonk flare ignition systems



flame front connection



Pilot Burner

Ignition of waste gas from pipe flares, air and steam assisted flares and ground flares

For most flare systems the pilot burner can not be accessed for service. Maintenance or replacement is not possible while the flare is in operation. To safeguard operation, Smitsvonk's pilots provide reliable ignition and stable burning even under the most difficult climate conditions.

Features

- High energy ignition
- Ignition by three integrated spark plugs
- Long lifetime, longer maintenance intervals
 Insensitive to moisture and dirt
- Complete delivery; cables, junction boxes and ignition unit
- Easy fit cable connectors
- Self-aspirating or forced air supply
- Integrated and protected thermocouple
- Functionally tested to client specifications
- Construction completely out of high temperature-resistant stainless steel

Applications

 Ignition of all kind of flares in the (petro) chemical, oil and gas, steel and biogas industry



Heavy duty pilot burner with radiation shield to protect the electrical connections



Pilot burners in different lengths and shapes

Common Data			
pipe diameter	2" (60 mm)	materials	mainly 310 SST
length	1200, 2326 or 2500 mm	windcap diameter	4", option 3"
design	angled or straight	mounting hooks	included
air requirement	self-aspirating	flame detection	by 6 mm thermocouple type K (T)
gas connection	1/2" BSPM	options	double thermocouple (DT),
supply gas	natural gas or propane/ butane, refinery gas (max. 40 vol% H ₂)		2 separate thermocouples (21)
options	refinery gas, up to 100% H ₂ , coke gas, biogas	-	



Pilot Burner Selection Table for Small and Medium Size Flares

Model Number	Design	Heat Release based on Natural Gas in kW	Gas Flow in nm³/hr	Required Pressure	Gas	Ignition	Thermocouple
ST60AF13-2326-360-25-TW length: 2326 mm	angled	10–17	1–1.7	0.5–1.5	natural gas or propane/ butane or refinery gas (max. 40% H ₂)	3 integrated spark plugs at flame side	single
ST60AF13-2326-360-25-DTW option for extra flame front ignition: ST60AF13-2326-360-25-TW-FFG						3 spark plugs and extra flame front tube	
ST60AF13-1200-TW length: 1200 mm	angled	10–17	1–1.7	0.5–1.5	natural gas or propane/ butane or refinery gas (max. 40% H ₂)	3 integrated spark plugs at flame side tube	single
option for thermocouple: ST60AF13-1200-DTW							double
ST60AF13-2500-360-25-TW length: 2500 mm	straight	10–17	1–1.7	0.5–1.5	natural gas or propane/ butane or refinery gas (max. 40% H ₂)	3 integrated spark plugs at flame side	single
option for thermocouple ST60AF13-2500-360-25-DTW option for extra flame front ignition: ST60AF13-2500-360-25-TW-FFG						3 spark plugs and extra flame front tube	double
ST60AF19-2326-360-25-TW length: 2326 mm	angled	15–29	1.5–2.9	0.2–0.8	natural gas or propane/ butane or refinery gas (max. 40% H ₂)	3 integrated spark plugs at flame side	single
option for thermocouple: ST60AF19-2326-360-25-DTW option for extra flame front ignition: ST60AF19-2326-360-25-TW-FFG						3 spark plugs and extra flame front tube	double
ST60AF19-2500-360-25-TW length: 2500 mm	straight	15–29	1.5–2.9	0.2–0.8	natural gas or propane/ butane or refinery gas (max. 40% H ₂)	3 integrated spark plugs at flame side	single
option for thermocouple: ST60AF19-2500-360-25-DTW option for extra flame front ignition: ST60AF19-2500-360-25-TW-FFG						3 spark plugs and extra flame front tube	duble
for biogas: ST60BF19-1200-T3 length: 1200 mm	straight	4–6 biogas	0.7–0.9	0.07–0.1	bio gas	3 integrated spark plugs at flame side	single
for coke gas: ST60WF-2326-360-25-TW length: 2326 mm	angled	15–25 coke gas	3–5	0.1–0.3	coke gas 40–60% H ₂ rest CO	3 integrated spark plugs at flame side	single
for low pressure: ST76(60)AF23-2326-360-25-TW length: 2326 mm	angled	15–23	1.5–2.3	40–100 mBarg	natural gas	3 integrated spark plugs at flame side	single

Straight construction





Pilot Burner Selection Table for Large Flares (Heavy Duty Applications)

Model Number	Design	Heat Release based on Natural Gas in kW	Gas Flow in nm ³ /hr	Required Pressure	Gas	Ignition	Thermocouple
HD60AF19-2326-360-25-TW length: 2326 mm	angled	24–30	2.4–3.0	0.5–0.9	natural gas or propane/ butane or refinery gas (max. 10% H ₂)	3 integrated spark plugs at 1.8 m from the top	single
option for thermocouple: HD60AF19-2326-360-25-DTW HD60AF19-2326-360-25-2TW option for extra flame front ignition: HD60AF19-2326-360-25-TW-FFG						3 spark plugs and extra flame front tube	double 2 pieces
HD60AF19-2500-360-TW length: 2500 mm	angled	24–30	2.4–3.0	0.5–0.9	natural gas or propane/ butane or refinery gas (max. 10% H ₂)	3 integrated spark plugs at 1.9 m from the top	single
option for thermocouple: HD60AF19-2500-360-DTW HD60AF19-2500-360-2TW							double 2 pieces
option for extra flame front ignition: HD60AF19-2500-360-TW-FFG						3 spark plugs and extra flame front tube	







Pilot Burner Inquiry Check List

Customer/Partner		Date
Contact		Preferred contact by
Project		Tel. Email
Location – country		

Plant Details

Plant type			
Flare tip type	 Pipe Flare High Pressure (Sonic) 	Steam Assisted	Air Assisted
Flare tip manufacturer			
Flare tip diameter	"	mm	
Total height complete flare stack			
Drawing of the flare tip available	◯Yes ◯No		
Waste gas flow	min	max	
Waste gas composition			
Pilot burners: required number	Pieces		
Pilot burners: ignition method	Flame Front	High Energy	C Flame Front and High Energy
Pilot gas pressure	min Barg	max Barg	
Pilot gas	ONatural gas	Propane	CLPG
Distance to flare tip from ignition / control unit			
Explosion proof required	Yes	No	
ATEX	Zone 1 Zone 2	Gas Group IIC Gas Group	p IIB
IECEx	Zone 1 Zone 2	Gas Group IIC Gas Group	p IIB
Power supply	230 VAC	○115 VAC	Other
Ignition cable	High temperature (775°C) ignition	n cable with connector and SST pro	tection hose
	○ 12 m	22 m	Other length
Thermo-couple cable	High temperature (775°C) thermo	-couple cable with connector and	SST protection hose
	○ 12 m	○ 22 m	Other length
SSt junction box for ignition signals	Yes No		
SSt junction box for T/C signals	Yes No		
Low temperature ignition cable	m		
Low temperature T/C cable	m		
Flame front generator panel required	⊖Yes ⊖No		



Continuous Electronic Spark Flare Ignition

Features

- No gas consumption; offering considerable savings
- Substantial reduction of investment costs since no gas lines, valves, instrumentation or electrical control system for the pilot burner are needed

Applications

- Coke oven flares
- Pipe flares with hydrogen in the waste gas
- Temporary flares from tank farms



Description

Smitsvonk has decades of experience with direct electric ignition of flare units. A reproducible, high energy, highly reliable spark (described in the literature as "plasma ignition") that is not susceptible to external influences such as moisture and dirt, guarantees the safe ignition and combustion of the residual gas in the flare.

Such direct electric spark ignition may, for example, be used in flares firing coke oven gas and flares where fuel gas containing a minimum of 6% hydrogen is burnt at relatively low flame velocities in the flare head.

In addition, the spark ignition module employed by Smitsvonk offers the decisive advantage of thyristor-controlled circuitry that is not subjected to wear and tear. The ignition system is designed to withstand the long operation and maintenance cycles typical for these types of industries.

The construction of the ignition lance depends on exit velocity, gas composition and the number of operation hours. The number of lances depends on the flare diameter.





Direct spark ignition of a coke oven flare



Ignition Lances

Direct ignition of (pilot) burners, flares and other processes

Features

- Built to client specifications
- High temperature resistance
- Long life time
- Easy fit cable connectors
- Insensitive to moisture
- Exchangeable spark plug







example of a straight ignition lance





Applications

Burners and flares

Options

- explosion proof versions
- for thermocouple
- for flexible lances
- for special bent lances
- for angled spark plug



Ignition Lances for Flares					
diameter	26.7 mm	26.7 mm	26.7 mm		
type	26.7T-L-A0-TK1818	26.7T-L-A0-TK181835	26.7T-LA90-TK1818		
construction	straight	angled spark plug	angled lance 45°		
length L	300–1000 mm: multiples of 100 mm, 1000–2000 mm: multiples of 100 mm, 2000–3000 mm: 200 mm intervals	300–1000 mm: multiples of 100 mm, 1000–2000 mm: multiples of 100 mm, 2000–3000 mm: 200 mm intervals	1500, 2000 or 2300 mm		
tube material	310 SST	310 SST	310 SST		
electrical connection	M30 easy fit connector	M30 easy fit connector	M30 easy fit connector		
mounting hooks	option	option	fixed or adjustable		
options	- thermocouple - explosion proof - ATEX II 2G Ex e IIC T6/T5	- thermocouple - explosion proof - ATEX II 2G Ex e IIC T6/T5	- thermocouple - explosion proof - ATEX II 2G Ex e IIC T6/T5		



Ignition Lances

For burners and processes



Accessories

- High temperature (775 °C) ignition cable with connector and SST protection hose
- High temperature (775 °C) thermocouple cable with connector and SST protection hose
- SST junction box for ignition or thermocouple signal
- Low temperature ignition cable
- Low temperature thermocouple cable
- Ignition and control unit (see pages 17 and 18)

Ignition Lances for Burners and Processes					
type	17.2-L-TP1412N-M25	17.2-L-TP1412-JB	15-L-TP12-JB		
diameter	17.2 mm	17.2 mm	15 mm		
design	straight	straight	straight		
length L	200–1000 mm: multiples of 100 mm, 1000–2000 mm: multiples of 100 mm, 2000–3000 mm: 200 mm intervals	200–1000 mm: multiples of 100 mm, 1000–2000 mm: multiples of 100 mm, 2000–3000 mm: 200 mm intervals	200–1000 mm: multiples of 100 mm, 1000–2000 mm: multiples of 100 mm, 2000–3000 mm: 2000 mm intervals		
tube material	310 SST	310 SST	316 SST		
electrical connection	I connection M25 easy fit connector material: 316 SST		junction box material: aluminium		
mounting hooks	hooks option		option		
option	 flexible lance special bent shape mounting adapter ATEX II2G EEx dllC T6 ATEX II 2G Ex e IIC T6/T5 M22 ATEX connector 12 mm and 10 mm diameter 316 SST Junctionbox 	 flexible lance special bent shape mounting adapter ATEX II/26 EEx dIIC T6 ATEX II 2G Ex e IIC T6/T5 M22 ATEX connector 12 mm and 10 mm diameter 316 SST Junctionbox 	flexible lance special bent shape mounting adapter ATEX II2G EEx dIIC T6 ATEX II 2G Ex ellC T6/T5 M22 ATEX connector 12 mm and 10 mm diameter 316 SST Junctionbox		

Spark Plugs

- All types of low tension high energy spark plugs to replace existing high tension systems
- Standard mechanical connection: M10, M14 and M18







Gas Fired Igniters Tube Ø54 mm

Ignition of main burners in furnaces, boilers, power plants and incinerators

Features and Benefits

- High energy ignition
- Insensitive to moisture
- Stainless steel construction
- Self-aspirating, forced air supply or combination
- For self-aspirating version no air supply line required
- Insensitive to pressure fluctuations
- Robust design
- For all kind of gases and pressures
- Integrated spark plug(s) and ionisation electrode
- Explosion proof version (ATEX) available

Applications

• Main burners of furnaces, boilers, incinerators and power plants



Self-aspirating Ignition Burner						
type for natural gas	54AV13JB-L-A-V2E	54AV13JB-L-A-V3E	54AV13JB-L-A-V5E			
heat release	80–132 kW	115–192 kW	185–305 kW			
type for propane	54PV13JB-L-A-V2E	54PV13JB-L-A-V3E	54PV13JB-L-A-V5E			
heat release	120–195 kW	170–285 kW	280–458 kW			
min. max pressure	0.5–1.5 Barg					
length L	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 100 mm intervals, 2000 to 4000 mm: 200 mm intervals					
air inlet A	165, 230 or 400 mm in step	os of 10 mm				
connection to main burner	Flange 2½" ANSI 150 LBS RF					
gas connection	1/2" NPTF					
air conn. for forced draft	1/2" BSPF					
ignition	by 3 integrated spark plug	S				
flame detection	ionisation					
tube material	310 SST					
connection material	316 SST					
electrical connection	General purpose connection	on housing				
protection	IP66					





Explosion Proof Self-aspirating Ignition Burner					
type for natural gas	54AV13EXE-L-A-VE	54AV13EXE-L-A-V2E	54AVD13-L-A-V5E		
heat release	46–75 kW	80–132 kW	185–305 kW		
type for propane	54PV13EXE-L-A-VE	54PV13EXE-L-A-V2E	54PVD13-L-A-V5E		
heat release	67–109 kW	120–195 kW	280–458 kW		
min. max. pressure	0.5–1.5 Barg				
length L	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 100 mm intervals 2000 to 4000 mm: 200 mm intervals				
air inlet A	165, 230 or 400 mm in steps of 10 mm				
connection to main burner	flange 2½" ANSI 150 LBS R	F			
gas connection	1/2" NPTF	1/2" NPTF	1/2" NPTF		
air conn. for forced draft	1/2" BSPF	1/2" BSPF	1/2" BSPF		
ignition	3 integrated spark plugs				
flame detection	ionisation				
tube material	310 SST				
connection material	316 SST				
electrical connection	explosion proof connectio	n housing			
protection	IP66				
explosion proof	ATEX II 2G Ex e IIC T5/6 DE	KRA11ATEX0032 (-40 to 80°	°C)		





Gas Fired Igniters Tube Ø54 mm

Ignition of main burners in furnaces, boilers, power plants and incinerators

Features and Benefits

- High energy ignition
- Insensitive to moisture
- Stainless steel construction
- Self-aspirating, forced air supply or combination
- For self-aspirating version no air supply line required
- Insensitive to pressure fluctuations
- Robust design
- For all kind of gases and pressures
- Integrated spark plug(s) and ionisation electrode
- Explosion proof version (ATEX) available

Applications

Main burners of furnaces, boilers, incinerators and power plants



Self-aspirating Ignition Burner					
type for natural gas	N54AV13-L-A-V2E	N54AV13-L-A-V3E	N54AV13-L-A-V5E		
heat release	80–132 kW	115–192 kW	185–305 kW		
type for propane	N54PV13-L-A-V2E	N54PV13-L-A-V3E	N54PV13-L-A-V5E		
heat release	120–195 kW	170–285 kW	280–458 kW		
min. max pressure	0.5–1.5 Barg				
length L	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 100 mm intervals, 2000 to 4000 mm: 200 mm intervals				
air inlet A	165, 230 or 400 mm in ster	os of 10 mm			
connection to main burner	Flange 2½" ANSI 150 LBS F	F			
gas connection	1/2" BSPF	3/4" BSPF	3/4" BSPF		
air conn. for forced draft	1/2" BSPF	1/2" BSPF	1/2" BSPF		
ignition	by 3 integrated spark plug	S			
flame detection	ionisation				
tube material	310 SST				
connection material	316 SST				
electrical connection	M25 connector for ignitition	on, M25 connector for ionisa	ation		
protection	IP65				



Explosion Proof Self-aspirating Ignition Burner					
type for natural gas	54AVD13-L-A-VE	54AVD13-L-A-V2E	54AVD13-L-A-V5E		
heat release	46–75 kW 80–132 kW 185–305 kW				
type for propane	54PVD13-L-A-VE	54PVD13-L-A-VE 54PVD13-L-A-V2E 54PVD13-L-A-V			
heat release	67–109 kW	120–195 kW	280–458 kW		
min. max. pressure	0.5–1.5 Barg				
length L	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 100 mm intervals 2000 to 4000 mm: 200 mm intervals				
air inlet A	165, 230 or 400 mm in ste	ps of 10 mm			
connection to main burner	flange 2½" ANSI 150 LBS R	F			
gas connection	1/2" NPTF	1/2" NPTF	1⁄2" NPTF		
air conn. for forced draft	1/2" BSPF	1/2" BSPF	1⁄2" BSPF		
ignition	3 integrated spark plugs				
flame detection	ionisation				
tube material	310 SST				
connection material	316 SST				
electrical connection	explosion proof connection	n housing			
protection	IP65				
explosion proof	ATEX II 2G EEx D IIC T6 PTE	303ATEX1190 /(-20 TO 60 D	EGREE C)		



Gas Fired Igniters Tube Ø48.3 mm

Ignition of main burners in furnaces, boilers, power plants and incinerators

Features and Benefits

- High energy ignition
- Insensitive to moisture
- Stainless steel construction
- Self-aspirating, forced air supply or combination
- For self-aspirating version no air supply line required
- Insensitive to pressure fluctuations
- Rugged design
- For all kind of gases and pressures
- Integrated spark plugs(s) and ionisation electrode
- Explosion proof version (ATEX) available

Applications

• Main burners of furnaces, boilers, incinerators and power plants



Self-aspirating Ignition Burner							
type for natural gas	L48AV18JB- L-A-V	48AV13JB -L-A-V	48AV13JB -LA-V2E	J48AV13JB -L-A-V4E	L48BF18JB- 1300-1210-T3		
heat release	17-31 kW	46–75 kW	80–132 kW	150–250 kW	Biogas		
type for propane	L48PV18JB- L-A-V	48PV13JB -L-A-V	48PV13JB- L-A-V2E	J48PV13JB- L-A-V4E	65–85 vol% CH4 heat release:		
heat release	22-39 kW	67–109 kW	120–195 kW	226–370 kW	4–5 kW		
min. max. pressure	0,2–0,8 Barg	0.5–1.5 Barg			15–40 mBarg		
length L	400, 500, 600: n from 1000 to 20 2000, 2500, 300	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 200 mm intervals, 2000, 2500, 3000 mm					
air inlet A	≥300 mm in ste	≥300 mm in steps of 10 mm					
connection to main burner	flange 2" ANSI 1	150 LBS RF					
gas connection	1⁄2" NPTF						
air conn. for forced draft	1⁄2" BSP						
ignition	integrated spar	k plug					
flame detection	ionisation 3 mm thermocouple						
tube material	310 SST						
connection material	316 SST						
electrical connection	connection hou	using					
protection	IP66						



Explosion Proof Self-aspirating Ignition Burner

type for natural gas	L48AV18EXE- L-A-V	48AV13EXE- L-A-VE	48AV13EXE- L-A-V2E	48AV13EXE- L-A-V4E
heat release	17-31 kW	46–75 kW	80–132 kW	150–250 kW
type for propane	L48PV18EXE- L-A-V	48PV13EXE- L-A-VE	48PVD13- L-A-V2E	48PVD13- L-A-V4E
heat release	22-39 kW	67–109 kW	120–195 kW	226–370 kW
min. max. pressure	0,2–0,8 Barg	0.5–1.5 Barg		
length L	400, 500, 600: multiples of 100 mm, from 1000 to 2000 mm: 200 mm intervals, 2000, 2500, 3000 mm			
air inlet A	≥300 mm in steps of 10 mm			
connection to main burner	flange 2" ANSI 150 LBS RF			
gas connection	1/2" NPTF			
air conn. for forced draft	1/2" BSPF			
ignition	integrated spark plug			
flame detection	ionisation			
tube material	310 SST			
connection material	316 SST			
electrical connection	explosion proof connection housing			
protection	IP66			
explosion proof	ATEX 2G Ex e IIC T5/6 DEKRA11ATEX0032 (-40 to 80° C)			



Igniter connection



Gas Fired Igniters Tube Ø38 mm

Ignition of main burners in furnaces, boilers, power plants and incinerators

Features and Benefits

- High energy ignition
- Insensitive to moisture
- Stainless steel construction
- Self-aspirating, forced air supply or combination
- No air supply line required for self-aspirating version
- Insensitive to pressure fluctuations
- Rugged design
- For all kind of gases and pressures
- Integrated spark plugs(s) and ionisation electrode
- Explosion proof version (ATEX) available

Applications

Main burners of furnaces, boilers, incinerators and power plants



Self-aspirating Ignition Burner		
type for natural gas	38AVS-L-A-VE	
heat release	17–29 kW	
type for propane	38PVS-L-A-VE	
heat release	24–39 kW	
min. max pressure	0.5–1.5 Barg	
length L	400, 500 600: multiples of 100 mm from 1000 to 2000: 200 mm intervals 2000, 2500, 3000 mm	
air inlet A	≥300 mm in steps of 10 mm	
connection to main burner	flange 1½" ANSI 150 LBS RF	
gas connection	½" NPTF	
air conn, for forced draft	option	
ignition	by 1 integrated spark plug	
flame detection	ionisation	
tube material	310 and 321 SST	
connection material	316 SST	
electrical connection	M25 connector for ignition, M25 connector for ionisation	
protection	IP65	



Explosion Proof Self-aspirating Ignition Burner		
type for natural gas	38AVEXE-L-A-VE	
heat release	17–29 kW	
type for propane	38PVEXE-L-A-VE	
heat release	24–39 kW	
min. max pressure	0.5–1.5 Barg	
length L	400, 500 600: multiples of 100 mm from 1000 to 2000: 200 mm intervals 2000, 2500, 3000 mm	
air inlet A	≥ 300 mm in steps of 10 mm	
connection to main burner	flange 1½" ANSI 150 LBS RF	
gas connection	½" NPTF	
air conn, for forced draft	1⁄2" BSPF	
ignition	integrated spark plug	
flame detection	ionisation	
tube material	310 and 321 SST	
connection material	316 SST	
electrical connection	explosion proof connection housing	
protection	IP66	
explosion proof	ATEX II 2G Ex e IIC T5/6 DEKRA11ATEX0032 (-40 to 80°C)	



Gas Fired Igniter (Ignition Burner) Inquiry Check List

Customer/Partner			Date
Contact			Preferred contact by
Project			Tel. Email
Location – country			
Plant Details			
Plant type			
Application	Furnace, natural draft	Furnace, forced draft	Boiler Incinerator
Heater / furnace draft	min	max	
Ignitor mounting position	Vertical	Horizontal	
Ignitor outer tube diameter	○ 48 mm○ other	○ 54 mm	38 mm
Total length			
Air sleeves position (A)			
Insert length			
Mounting flange	2" ANSI 150 LBS RF	2 1/2" ANSI 150 LBS RF	Special plate flange
Drawing of the main burner available	⊖Yes ○No		
Explosion proof (ignitor) required	⊖Yes ○No		
ATEX	Zone 1 Zone 2	Gas Group IIC Gas Gro	up IIB
Gas pressure	min Barg	max Barg	
Ignitor gas	Natural gas	Propane	
	Other, gas composition rec	quired	
Required heat release	kW		
Required flame length			
Flame detection	lonisation	OBy external flame scanner	
Frequency in use	Continuously		
Combustion air	◯ self aspirating	forced draft	
Will preheated combustion air be fed to the gas fired ignitor	○No ○Yes	°℃	
Windbox pressure	min	max	
Ambient air temperature	○-20 to 60°C	-40 to 80°C	─ -40 to 70°C
Distance to ignition unit			
Power supply ignition unit	230 VAC	115 VAC	Other
Explosion proof (Ignition Unit) required	Yes	No	
ATEX	Zone 1 Zone 2	Gas Group IIC Gas Gro	up IIB

Gas Group IIC Gas Group IIB

Zone 1 Zone 2



Ignition Units

Ignition and burner control for ignition burner, pilots burners, lances and spark plugs

Features and Benefits

- High energy ignition
- Capacitor discharge with thyristor/diode
- 100% Electronic, no wear
- Wide range of power supply voltages.
- Low power consumption
- No limitation for cable length for flare ignition units

Applications

- Furnaces
- Boilers
- Incinerators







Ο

0

0

 \bigcirc







Ignition units for igniters of furnaces, boilers and incinerators		
type	E-LIGHT-162609	E-LIGHT-233311-SV98H-CR
function	ignition	ignition, flame detection and remote start
spark energy	2 J	2 J
spark voltage	2000 V	2000 V
spark frequency	2 Hz	2 Hz
power supply	230, 115 or 24 VAC 50–60 Hz	230, 115 or 24 VAC 50–60 Hz
power consumption	15 VA	22 VA
housing	aluminum	aluminum
dimensions LxWxH	260 x 160 x 90 mm	230 x 330 x 110 mm
protection	IP66	IP66
remote start relay	n/a	24, 48 VDC, 110 or 230 VAC
flame relay	n/a	ionisation SV98H
max. cable length	30 m	30 m
Explosion proof, same specification only different dimensions		
type	E-LIGHT-GUB03	E-LIGHT-GUB03-SV98H-CR
explosion proof	ATEX II 2G Ex d IIC T6	ATEX II 2G Ex d IIC T6
dimensions LxWxH	276 x 276 x 217 mm	276 x 276 x 217 mm



Ignition Units

Ignition and burner control for ignition burners, pilots burners, lances and spark plugs





Ignition Units for Igniters of Furnaces, Boilers and Incinerators		
type	BWO(BG) 2/2 SV98H-CR	
function	ignition, flame detection and remote start	
design	Ex d housing for ignition unit and relays	
	Ex e housing for terminals	
spark energy	appr. 8 J	
spark voltage	2000 Volt	
spark frequency	2 Hz	
power supply	230, 115 or 24 VAC 50–60 Hz	
power consumption	37 VA	
housing	Cast Aluminium (Ex d) - 316 SST Exe	
dimensions	605 x 235 x 268 mm	
protection	IP 66	
remote start relay	24 VDC	
flame relay	ionisation SV98H	
explosion proof	ATEX II 2G Ex de IIC T6	

Ignition Units for Pilot Burners of Flares (longer distance) Common Data		
function	ignition and flame detection for pilot burner(s) or ignition lance(s)	
power supply	230, 115 or 24 VAC 50–60 Hz, option: for DC or battery back-up	
ignition	100% electronic, type SVECU	
spark energy	SVECU : 9 or 18 J E-SPARK: 4 J	
spark voltage	SVECU : 3000 V	E-SPARK: 2000 V
spark frequency	0,5 or 2 Hz depending on type pilot burner or lance.	
flame detection	thermocouple relay type K	
control	by small PLC	
enclosure	IP66 general purpose or explosion proof (ATEX), option: explosion proof for IIC	
material	painted steel for IP66 enclosure, cast aluminium for ex-proof enclosure, option: SST enclosure	
LED signal lamps	yellow power on, green for pilot on, red for pilot off, red for ignition failure	
switches	main power isolator, start, stop, reset and lamp test	
contacts	pilot on/off, ignition failure, option for 4–20 mA	

	for one pilot burner	for two pilot burners	for three pilot burners
type	SVECU X/2-EJB5- H4D4ST-L-CR	2 SVECU X/2-2EJB5- H4D6S2T-L-CR	3 SVECU X/2-2EJB5- H4D8S3T-L-CR
construction	1 Ex d housing	2 Ex d housing	2 Ex d housings
number of ignition units	1	2	3
max. distance	250 m	250 m	250 m
option for	500 m	500 m	500 m option: for more pilot burners

	for one pilot burner	for two pilot burners	for three pilot burners
type	E-SPARK X/2-EJB5- H4D4ST-L-CR	E-SPARK X/2-2EJB5- H4D6S2T-L-CR	E-SPARK X/2-2EJB5- H4D8S3T-L-CR
construction	1 Ex d housing	2 Ex d housing	2 Ex d housings
number of ignition units	1	2	3
max. distance	70 m	70 m	70 m



Portable Ignition Units

Lightweight, battery operated ignition unit



Schematic



Portable Ignition Units		
type	SPI	
ignition type	high energy	
spark frequency	3 Hz	
battery type	reloadable 12 V	
battery capacity	3.2 AH (suitable for 3 hours of continuous operation)	
protection class	IP65	
housing material	aluminum	
total weight (L=1000 mm)	6 kg	
battery charger power supply	220–240 VAC	
power consumption	17 W	
loading time	300 min	



Semi Portable Ignition Unit

Explosion proof ignition unit with ignition lance to ignite main burner in furnaces or boilers. Ignition can be controlled by a remote switch

Features

- Explosion proof ignition unit
- High energy ignition
- Operation controlled by remote switch
- Easy to handle

Application

• Direct spark ignition for industrial burners in absence of fixed igniters



Semi Portable Ignition Unit	
ignition	high Energy
spark energy	2 J
spark voltage	2 kV
spark frequency	2 Hz
power supply	220–240 VAC 50–60 Hz, option 24 VAC or 115 VAC
power consumption	37 VA
protection class	IP66
explosion proof	ATEX II 2G Ex d IIC T6
housing material	aluminum
lance material	316 SST
handgrip material	aluminum
lance diameter	15 mm
lance length L	500–2000 mm, in steps of 100 mm
option	bent lance



Mobile Ignition Units

Ignition of main burners at places where a fixed pilot burner or igniter is not available and a spark is insufficient to ignite the main burner

Features

- High energy ignition unit
- Insensitive to moisture and dirt
- Self-aspirating SST igniter
- Available for different gases and pressures

Application

- Furnaces
- Boilers
- Ground flares



2-wheeled trolly



4-wheeled trolly

Mobile Ignition Units	
2-wheeled trolly	4-wheeled trolly
consisting of:	consisting of:
self-aspirating igniter type 7 diameter: 38 mm length: 1000 mm (other lengths possible) capacity: 20 kW gas: propane igniter materials: 316 and 321 SST	self-aspirating igniter type 51 diameter: 48 and 51 mm length: 1000 mm (other lengths possible) capacity: 180–350 kW gas: propane igniter materials: 310 and 316 SST
explosion proof (ATEX 3G IIB) high energy ignition unit	explosion proof (ATEX 2G IIC) high energy ignition unit
explosion proof switch	explosion proof switch
explosion proof solenoid valve	explosion proof solenoid valve
pressure reducer with downstream pressure gauge	pressure reducer with downstream pressure gauge
2 reels, including all cabling and gas hose	2 reels, including all cabling and gas hose
11 m gas hose and ignition cable	11 m gas hose and ignition cable
25 m power supply cable	25 m for power supply cable
suitable for 24, 120 or 230 VAC	suitable for 24, 120 or 230 VAC
IP 66 enclosure for instruments	IP 66 enclosure for instruments
not included: gas bottles	not included: gas bottles
options: - igniter diameter 25 mm (not for natural gas) - ionisation flame detection - LPG, butane, natural gas or refinery gas	options: - wall mounted version with longer cable lengths - ionisation flame detection - LPG, butane, natural gas or refinery gas



Complete Systems / Skids / Engineered Products

- Small (biogas flares)
- Gas and Air control skids acc EN746
- Blower skids for combustion air. Pneumatic retraction units
- Control units with PLC's acc. ATEX or IECEx certification







Biogas Flares

Type Half open, emergency Pressure: 3 mbarg or 35 mbarg Capacity: DN50 – 60 nm³/hr DN65 – 80 nm³/hr DN80 – 125 nm³/hr DN100 – 250 nm³/hr





Gas Flares for Events, Shows and Memorials

The high quality and safety of Smitsvonk products also allows applications outside the industry. Fire keeps people in suspense, appeals to the senses and evokes emotion.

Big events or shows are often spectacularly designed and staged with fire. The high safety standards at public events require careful planning, sophisticated technology and the corresponding know-how. Smitsvonk has decades of experience in the ignition and use of torches with thousands of installations around the world. Our products are designed for extreme conditions. They run at high temperature fluctuations, humidity and high soil load 24-hour around-the-clock – ideal also for safe use in public places.

Do you have a fiery idea for your next spectacular show? Contact us!













SMITSVONK Holland B.V.

P.O. Box 180, 2700 AD Zoetermeer Goudstraat 6, 2718 RC Zoetermeer Netherlands Tel. +31 79 361 35 33 Fax +31 79 361 13 78 E-Mail: sales@smitsvonk.nl www.smitsvonk.nl

DURAG

DURAG GmbH Kollaustraße 105 22453 Hamburg, Germany Tel. +49 40 55 42 18-0 Fax +49 40 58 41 54 E-Mail: info@durag.de

Keywein

Hegwein GmbH Am Boschwerk 7 70469 Stuttgart Germany Tel. +49 711 135 788-0 Fax +49 711 135 788-5 E-Mail: info@hegwein.de

DURAG Brazil

DURAG Siena do Brasil Ltda Rua Vinte e Dois de Agosto, 66 Diadema - SP 09941-530 Brazil Tel. +55 11 4071-5050 r.28 Fax +55 11 4077-1718 E-Mail: info@duragsiena.com.br

DURAG Instrumentation (Shanghai) Co., Ltd. Room 706, Dibao Plaza, No. 3998 Hongxin Rd., Minhang District, Shanghai, 201103 PR China Tel. +86 21 60732979-206 Fax +86 21 60732980 E-Mail: info@durag-cn.com

DURAG RUSS OOO

Andropova avenue 18/6, Office 2-03 115432 Moscow Russia Tel. +7 499 4180090 Fax +7 499 4180091 E-Mail: info@durag-group.ru

DURAG data systems GmbH Kollaustraße 105, 22453 Hamburg, Germany Tel. +49 40 55 42 18-3000 Fax +49 40 55 42 18-3099 E-Mail: info@durag-data.de



A Brand of **DURAG GmbH** Kollaustraße 105 22453 Hamburg, Germany Tel. +49 40 55 42 18-0 Fax +49 40 58 41 54 E-Mail: verewa@durag.de

DURAG France S.a.r.l.

Parc GIP Charles de Gaulle 49, rue Léonard de Vinci, BP 70166 95691 Goussainville CEDEX, France Tel. +33 1 301 811 80 Fax +33 1 393 383 60 E-Mail: info@durag-france.fr

DURAG Italia S.r.l.

Via Carlo Panseri, 118 CIM uffici, P. secondo 28100 Novara Italy Tel. +39 0321 679569 Fax +39 0321 474165 E-Mail: info@durag.it

DURAG UK GmbH

Lullington House, Ashby Road Burton-on-Trent, Staffordshire, E15 0YZ Great Britain Tel. +44 1283 553 481 Fax +44 1785 760 014 E-Mail: durag.uk@durag.de

DURAG process & systems technology gmbh Kollaustraße 105 22453 Hamburg, Germany Tel. +49 40 55 42 18-0 Fax +49 40 58 41 54 E-Mail: info@durag-process.de



DURAG Siena do Brasil Ltda Rua Vinte e Dois de Agosto, 66 Diadema - SP 09941-530 Brazil Tel. +55 11 4071-5050 r.28 Fax +55 11 4077-1718 E-Mail: info@duragsiena.com.br

DURAG, Inc., USA

1355 Mendota Heights Road Suite 200 Mendota Heights MN 55120, USA Tel. +1 651 451-1710 Fax +1 651 457-7684 E-Mail: durag@durag.com

DURAG Japan Office

c/o TMS Planning Inc. 291-2 Umena, Mishima-shi, Shizuoka-ken, 411-0816 Japan Tel. +81 55 977 3994 Fax +81 55 977 3994 E-Mail: info@durag.jp

DURAG India Instrumentation Private Limited

#27/30, 2nd Main Road Industrial Town, Rajajinagar Bengaluru 560 044, India Tel. +91 80 2314 5626 / 4215 1191 Fax +91 80 2314 5627 E-Mail: info@duragindia.com

DURAG Korea Office

RM #1131, Manhattan Building, 36-2, Yeouido-Dong, Yeongdeungpo-Gu, Seoul, Korea Tel. +82 2 761 8970 Fax +82 2 761 8971 E-Mail: info@durag-group.co.kr

