

Revealing insights.

ECO Series

Low weight portable
X-ray systems



comet
x-ray

ECO Series

Economize on effort with the perfect tool for the job

Getting quality data from your portable NDT process requires a high degree of accurate manipulation and positioning by the onsite technician. Whether it's seam-testing on pipelines or checking aviation component integrity, there's no way that getting good results isn't going to involve some physical effort.

That's why we've designed the new ECO with lower weight and to be more manageable - even for just one person. With its robust, ergonomic design and weight of just 14 kg, the ECO has been designed to make workflows faster, safer and less tiring. And of course, because the ECO is built using the same principles, as the tried and trusted EVO series, there's no compromise on image quality.

When you need the right tool for the job, the ECO delivers where it counts. With its rugged, low weight and accurate performance, you simply get more from your working day with less effort.



» We could see that there was a trend towards low weight portable X-ray equipment, in a quality that supported professional use - that is the main reason for the creation of the ECO series.

Low weight and high quality.

Jan Bressendorff, ECO Product Manager

1

The future is ECO – less lead, less weight

We called it ECO for a reason. As well as economizing on the required user effort with its low weight composite material structure, we've made the unit even more eco-friendly. By reducing the number of lead (Pb) components, we've not just cut weight but made the unit more environmentally friendly.

2

A solid investment

The ECO makes good economic sense too: As a one-man tool, you reduce labor costs, get a faster and smarter workflow as it's easier to handle and carry - while the small focal spot gives the possibility of shorter exposure times and increased image quality.

That's what we call economical.

3

Makes work flow

Creating a smarter workflow for portable X-ray has been our driving force behind the development of the ECO. With its unique length-to-width ratio, ergonomic design, and well distributed 14 kg, the unit requires less effort to handle and re-position - even for just one person.

A broad operating temperature range from -20°C to +50°C makes the ECO reliable even in extreme environments, while its intuitive interface allows for an even smarter workflow.

4

Rugged and reliable

The ECO is designed and built in Denmark using refined EVO technology. With the best components, including new low weight composite materials, the units are assembled with the utmost care - making them reliable, long-lasting, and a sound economical investment.


Protected by a sturdy, robust casing is a high-quality metal ceramic X-ray insert. The systems meet IP65 standards and are fully operational in dusty and wet conditions.

5

Safe and accurate

Each unit is individually tested and measured for safety and accuracy to meet the highest international safety standards - including RoHS.

The ECO series features a 1.0 mm small focal spot and 750 W constant potential X-ray power ensuring high performance, shorter exposure times, and high-resolution results.





Specifications

	ECO 160DS	ECO 200DS
Weight	13 kg	14 kg
Height	610 mm	637 mm
Focal spot size EN 12543	1.0 mm	1.0 mm
High voltage adjustment	20 - 160 kV	30 - 200 kV
mA adjustment	0.5 - 7.0 mA	0.5 - 6.0 mA
Max. X-ray power	750 W	750 W
Beam angle	40° x 60°	40° x 60°
Leakage radiation	Max. 2.0 mSv/h	Max. 2.0 mSv/h
Environment	IP65	IP65
Temperature range	-20°C to +50°C	-20°C to +50°C

Smart accessories

In our world, time is everything. The smarter we help you and your people work, the faster and better you'll get the job done. Working smart means accuracy, safety and reliability, and most important, it means avoiding costly disruptions to your workflow.

A broad range of high-quality accessories is available for the ECO series. These various accessories enable a smarter workflow and support multiple applications in all environments.

Our range of accessories makes the use of portable X-ray equipment safer, more efficient and convenient when challenging working conditions has to be solved.

The accessories are not only designed to be used in rough conditions but also to be agile and user-friendly for customers when using portable X-ray systems.

Flight Case ECO Tube Heads



3-Legged Tube Stand



4-Legged Tube Stand



Flight Case CONTROL EVO



You can find us here

Switzerland (Head Office)

COMET AG Industrial X-ray modules
Herrengasse 10
3175, Flamatt
T +41 31 744 90 00

United States

COMET Technologies USA Inc.
100 Trap Falls Road Extension
Shelton, CT 06484
T +1 203 447 31 65

Denmark

COMET Technologies Denmark A/S
Helgeshøj Alle 38
2630, Taastrup
T +45 72 40 77 00

China

COMET Mechanical Equipment Co. Ltd.
1201 Guiqiao Road
Building 10, 1st Floor
Pudong, Shanghai 201206
T+86 21 6879 9000

Japan

COMET Technologies Japan KK
New Stage Yokohama Bldg., 1st Floor
1-1-32 Shinurashima-cho
Kanagawa-ku
Yokohama, 221-0031
T +81 45 450 1730

South Korea

COMET Technologies Korea Co., Ltd.
Suwon Venture Plaza Bldg, Room 402
48 Samsung-ro, 168 beon-gil,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16676
T +82 (0)70 4337 1282
T +82 (0)70 4332 1580

COMET Technologies Denmark A/S

Helgeshøj Alle 38, 2630 Taastrup, Denmark
T +45 72 40 77 00
VAT DK 18 21 52 33
Web: xray.comet.tech
Mail: mail.xray.dk@comet.tech

comet
x-ray